

DB25GMT Starry Varius





DB25GMT Starry Varius

Technical specifications

Name: DB25GMT Starry Varius

Reference: DB25VGTIS3

Functions: Hours, Minutes, Second time zone (GMT),

Day/night indicator, Jumping date

Movement: DB2507

Type: Mechanical hand-wound movement

Adjustment: Winding, setting the local and travel time (GMT) by

means of the crown (3 positions) - Secure

bidirectional systems

Via a corrector at 6 for the date hand (clockwise)

Technical features of calibre DB2507

Number of parts: 368

Jewelling: 40 jewels Diameter: 30 mm

Power reserve: 5 days, ensured by a self-regulating twin barrel

A De Bethune Innovation (2004)

Specificities: Titanium balance wheel with white gold inserts, optimised

for temperature differences and air penetration

De Bethune Patent (2016)

"De Bethune" balance-spring with flat terminal curve

De Bethune Patent (2006)

Silicon escape wheel

Microsphere Day/night indicator in rose gold and

blued steel similar decoration technic of the

spherical moon phase - De Bethune Patent (2004)

Triple pare-chute shock-absorbing system

De Bethune Innovation (2005)

Frequency: 28,800 vibrations per hour

Adornment: Curved mirror-polished steel plate cover

Steel barrel bridge cover, mirror-polished and adorned with "Côtes *De Bethune*" enhanced with microlight decoration in its center – *De Bethune*

innovation 2016

Hand snailed barrels

Hand-polished, chamfered steel parts



Display

Display: Hand-polished flamed-blued steel curved hands

Hand-polished flamed-blued date hand with

polished end

Day/night indicator in rose gold 5N and blued steel of the microsphere – similar decoration technic of the spherical moon phase – *De Bethune Patent*

(2004) date

Dial and flanges: Silver-toned curved date ring with polished and blue

markers

Silver curved hour ring

Rose gold curved minute ring

Silver 24h sub-dial with two-tone decals

Central dial in 2 parts: blue polished titanium with white gold pins/radiant silver microlight decoration

with a sunburst insert in polished rose gold

Case and strap

Case material: Titanium
Case diameter: 42 mm
Case thickness: 11,8 mm

Lugs: Integrated, hollowed lugs

Crystal: In sapphire crystal (1800 Vickers hardness) with

double anti-reflective coating

Case back: Open back in polished titanium and sapphire crystal

(1800 Vickers hardness) with double anti-reflective

coating

Water-resistance: 3 ATM

Strap: Extra-supple alligator leather, alligator lining

Buckle: Pin buckle in titanium